

Ρ λ ε Μ Ö

	r	M		6	
				6	
J1	J1-1	24V ḡ	Ö		150mA
	J1-2	24V ḡ			
	J1-3	CAN H			
	J1-4	CAN L			
J2	J2-1	p	p ḡ Ö	OC	DC24V ↓ 20mA
	J2-2	24V			
	J2-3	24V			
	J2-4	p ḡ		↓ ↓	
J3	J3-1	ḡ	ḡ ḡ Ö	OC	DC24V ↓ 20mA
	J3-2	24V			
	J3-3	24V			
	J3-4	ḡ ḡ		↓ ↓	
J5	J5-1	p L	L L	ε ^[1] ε ^[2]	DC5A24V AC5A250V
	J5-2	ḡ L			
	J5-3	L " í			
	J5-4	L			
	J5-5	L			
	J5-6	24V	ε		
	J5-7	24V			
J6	J6-1		ḡ Ö	OC	DC24V ↓ 20mA
	J6-2	24V			
	J6-3	24V			
	J6-4	ḡ ^[4]		↓ ↓	

F 64 r

4.1 1

i 2

π

w,

P

ñ

r

'

i

z

1

64

r

2

i

'

H

i

ñ

z

r

4.2 2

2 N

N Ü W E 0 L

“

e

1 L

e

2 L

“

e' []

e N

W e E 0

E N Ü 0 1 W I L

t e

M

H`

M

Ж

N Ü 2 W I L

t e L

M

H` r

到站灯脉冲间隔时间



数时持续输出...

到站灯信号

N取1值: 到站灯有



N取2值: 到站灯按脉冲间隔时间输出一次



到站灯条件成立

6.4

3

Q

3 N

N Ü W E 0

Q

1

Q

e N

W E 0

6.4

4

r L

4 N

r L

EN*0.5

N Ü W E 0-8

e N

W e E 0

i Ü W 0

i~

||

L

M

p r`

r`

r`

r`

r`

Er

6.5

5

H

5 N

p

r`

,3

N

π

,N n 3

Ü e 0

H

π

r`

r`

6.6

6

H

i

6 N

p

r`

,3

i

i i i

P i

i

X N

• m i

r`

N π

3

3 Ü L 0

i

L

X i

i Σ

i

r`

1 E`

r`

3 A

r`

i

Σ i

F

i

r`

2 E`

r`

γ CAN

X i

r`

i

[1]

t r`

D

i

i

W r`

r`